



Paralu Slim 34 is a non thermal break exterior minimal sliding system . The 20 mm vertical profile is the only unifying element, and is almost imperceptible between the glass panels.

It comes in a wide range of formats such as fixed, sliding, pocket and corner. This system also includes a variety of add-ons, finishes and it can be completely automated. This double glazed product can achieve surfaces of up to 12 m².

Main Advantages:

- Concealed frame in walls
- Handle with multipoint locking system

Sliding System

Type of Opening

Fixed	Sliding	Invisible	Pocket	Corner
Monorail	•		•	•
Birail	•	•	•	•
Multirail	•	•	•	•

Architectural Aspect

Vertical Profile	20mm/30mm
Max. Leaf Height	4000mm
Max. Leaf Width	4000mm
Max. Weight	Up to 600Kg
Max. Glazed Area	Double glazing up to 12 m ²
Glass Thickness	32mm

Performance

Light Transmission	Up to 98%
Security (ENV 1627)	RC2/WK2
Sound Insulation (EN ISO 717-1)	41 dB
Water Tightness (EN 12208)	Class E900
Air Permeability (EN 12207:2000)	Up to 600 Pa Class 4
Wind Load Resistance (EN 12210:2000)	Up to 1400 Pa Class 4B
Dimensions of tested sample	4000x3500mm

